

MODEL: RS300P




Rating power 300W	Surge power 600W
DC Input 12V/24V/48V	AC Output 110V/230V
Frequency 50/60Hz	Efficiency 88%-94%
THD <3%	No load current draws <0.35A
USB port 5V/2.1A	Start feature Soft start
Cooling fan By load & Temp.	Remote control Optional
Product dimension 160×150×70mm	Q'ty/CTN 6PCS
CTN size 45×31×36cm	CTN:N.W./G.W.(KG) 8.25/10.9KG

MODEL: RS1000P



Rating power 1000W	Surge power 2000W
DC Input 12V/24V/48V	AC Output 110V/230V
Frequency 50/60Hz	Efficiency 88%-94%
THD <3%	No load current draws <0.57A
USB port 5V/2.1A	Start feature Soft start
Cooling fan By load & Temp.	Remote control Optional
Product dimension 310×150×70mm	Q'ty/CTN 4PCS
CTN size 43.5×41.5×29cm	CTN:N.W./G.W.(KG) 12/15KG

MODEL: RS500P



Rating power 500W	Surge power 1000W
DC Input 12V/24V/48V	AC Output 110V/230V
Frequency 50/60Hz	Efficiency 88%-94%
THD <3%	No load current draws <0.42A
USB port 5V/2.1A	Start feature Soft start
Cooling fan By load & Temp.	Remote control Optional
Product dimension 210×150×70mm	Q'ty/CTN 6PCS
CTN size 42×34×44cm	CTN:N.W./G.W.(KG) 13.4/16.8KG

MODEL: RS1500P



Rating power 1500W	Surge power 3000W
DC Input 12V/24V/48V	AC Output 110V/230V
Frequency 50/60Hz	Efficiency 88%-94%
THD <3%	No load current draws <0.63A
USB port 5V/2.1A	Start feature Soft start
Cooling fan By load & Temp.	Remote control Optional
Product dimension 290×220×75mm	Q'ty/CTN 2PCS
CTN size 43×30.5×37cm	CTN:N.W./G.W.(KG) 8.6/10.9KG

MODEL: RS2000P



Rating power 2000W	Surge power 4000W
DC Input 12V/24V/48V	AC Output 110V/230V
Frequency 50/60Hz	Efficiency 88%-94%
THD <3%	No load current draws <0.67A
USB port 5V/2.1A	Start feature Soft start
Cooling fan By load & Temp.	Remote control Optional
Product dimension 320×220×75mm	Q'ty/CTN 2PCS
CTN size 45.5×30×36cm	CTN:N.W./G.W.(KG) 10.6/12.8KG

MODEL: RS3000P



Rating power 3000W	Surge power 6000W
DC Input 12V/24V/48V	AC Output 110V/230V
Frequency 50/60Hz	Efficiency 88%-94%
THD <3%	No load current draws <0.81A
USB port 5V/2.1A	Start feature Soft start
Cooling fan By load & Temp.	Remote control Optional
Product dimension 360×220×145mm	Q'ty/CTN 1PCS
CTN size 55×34×25cm	CTN:N.W./G.W.(KG) 8.2/9.8KG

MODEL: RS2500P



Rating power 2500W	Surge power 5000W
DC Input 12V/24V/48V	AC Output 110V/230V
Frequency 50/60Hz	Efficiency 88%-94%
THD <3%	No load current draws <0.73A
USB port 5V/2.1A	Start feature Soft start
Cooling fan By load & Temp.	Remote control Optional
Product dimension 380×220×75mm	Q'ty/CTN 2PCS
CTN size 50×30.5×36cm	CTN:N.W./G.W.(KG) 12/14.5KG

Mass solar
美日新能源